

DP-46

DMR DIGITAL RADIO

FM TRANSCEIVER

數位/類比
雙模機

專業數位無線電對講機

通訊內容嚴密保障

語音資料同頻道傳輸

頻道容量加倍提升

TDMA分時多工存取

糾錯技術完整傳輸



技術規格:

General

| | |
|-----------------------|---------------------------------|
| Frequency Range | UHF:400~480MHz |
| Channel Capacity | 32channels |
| Weight | 247g (with battery pack) |
| Operating Voltage | 7.4V DC |
| Battery Life | 1800mAh |
| Frequency Stability | ± 2.5ppm |
| Operating Temperature | -20°C~ +60°C |
| Size | 128x61x40mm (with battery pack) |

Transmitting Part

| | |
|------------------------|--|
| Power Output | 5W/1W |
| Modulation limit | 2.5KHz@12.5KHz (Narrow Band); 5.0KHz@25KHz (Wide Band) |
| Adjacent Channel Power | ≥ 70dB (Narrow Band); ≥ 70dB (Wide Band) |
| Hum & Noise | ≥ 36dB (Narrow Band); ≥ 40dB (Wide Band) |
| Spurious Emission | ≤ -36dB (Narrow Band); ≤ -36dB (Wide Band) |
| Error rate | ≤ 3% |
| Audio Distortion | ≤ 5% |

Receiving Part

| | |
|------------------------------|--|
| Sensitivity (12dB SINAD) | ≤ 0.25 μ V (Narrow Band); ≤ 0.20 μ V (Wide Band) |
| Audio Power Outout | 500mW/16Ω |
| Adjacent Channel Selectivity | ≥ 60dB (Narrow Band); ≥ 65dB (Wide Band) |
| Intermodulation | ≥ 60dB (Narrow Band); ≥ 60dB (Wide Band) |
| Spurious Rejection | ≥ 70dB (Narrow Band); ≥ 70dB (Wide Band) |
| Audio Distortion | ≤ 5% |
| Hum & Noise | ≥ 40dB (Narrow Band); ≥ 40dB (Wide Band) |

配件:



利滙科技股份有限公司

客服專線:0800-012800

<http://www.adicomm.com.tw>

授權經銷商:

